




شركة البابتين لصناعة البلاستيك والمواد العازلة المحدودة
AL BAPTAIN PLASTIC & INSULATION MATERIALS MFG. CO. LTD





ALBAPTAIN



EN ISO 9001:2015




ISO 14001:2015

Since 1979

L-RING CLOSE & OPEN TOP DRUMS

The L- Ring design makes handling easier and adds strength



220 ltr



220 ltr

AL- BABBAIN / MAUSER L- Ring High density (HDPE) Polyethylene drum of 220 Liter Nominal Capacity represents a major development in packing in Kingdom of Saudi Arabia. Our drums are used to store and transport liquids and other materials for a variety of different industries.

These drums provide many advantages:

- (1) Extremely strong and rigid product, easy to handle.
- (2) Safe and secure closure system, offer higher security during storage and transportation.
- (3) Metal over caps are available on request.
- (4) More durable than steel, will not dent, free from rust or corrosion.
- (5) Ability to withstand outdoor storage in high ambient temperatures.
- (6) Made according to international standards.
- (7) UN approved for transportation of hazardous materials.
- (8) Efficient drum design of body (100% Leak Proof)
- (9) Long life service (Reliability).
- (10) Chemical compatibility with hazardous and non-hazardous liquids.
- (11) Save warehouse space because they are stackable.

Specific and detailed information is available from Al-Babtain Plastic Barrel Div.

| Product | Capacity (Liters) | Overall Dimensions | | Weight (Kg) | Minimum Wall Thickness (mm) | CAPS |
|----------------|-------------------|--------------------|-------------|------------------|-----------------------------|----------|
| | | Diameter (mm) | Height (mm) | | | |
| CLOSE TOP Drum | 220 | Ø 581 \pm 5 | 935 \pm 5 | 9.0 \pm 0.150 | 2.70 | 2" Bungs |
| OPEN TOP Drum | 220 | Ø 581 \pm 5 | 935 \pm 5 | 7.50 \pm 0.150 | 2.50 | PE - LID |

OPEN TOP DRUMS & BUCKETS



120 ltr

50 ltr

40 ltr

30 ltr

20 ltr

The heavy weight 120 LTR, 50 LTR, 40 LTR, and 30 LTR Open Top drums, blow molded with high density polyethylene in different colors, having integral hand grips. The lid for open top drums is injection molded in different color with high density polyethylene.

The lid is secured by an efficient lever action locking coated metal band. Gasket in the lid made from specially formulated cellular rubber, which prevents leakage even the lid is under pressure.

| Product Type | Capacity (Liters) | Overall Dimensions | | Weight (Kg) | Minimum Wall Thickness (mm) | Stacking |
|---------------|-------------------|--------------------|-------------|-------------------|-----------------------------|----------|
| | | Diameter (mm) | Height (mm) | | | |
| Open Top drum | 120 | Ø 500 | 816 | 4.500 \pm 0.140 | 3.00 | 4 High |
| Open Top drum | 50 | Ø 374 | 605 | 1.800 \pm 0.50 | 1.80 | 2 High |
| Open Top drum | 40 | Ø 374 | 505 | 1.450 \pm 0.30 | 1.60 | 2 High |
| Open Top drum | 30 | Ø 374 | 410 | 1.100 \pm 0.30 | 1.20 | 2 High |
| Bucket | 20 | Ø 303 | 366.5 | 0.850 \pm 0.20 | 1.70 | 2 High |

CLOSED TOP DRUMS



120 ltr



60 ltr

The heavy weight 120 LTR and 60 LTR. Closed Top drums blow molded with high density polyethylene having integral hand grips, fitted with two bungs. (70mm & 38mm). These multi drums are extremely safe and strong.

| Product Type | Capacity (Liters) | Overall Dimensions | | Wall Thickness (mm) | Weight (Kg) | Stacking |
|-----------------|-------------------|--------------------|-------------|----------------------|---------------|----------|
| | | Diameter (mm) | Height (mm) | | | |
| Closed Top drum | 120 | Ø 500 | 783 | 3.00 | 4.800 ± 0.150 | 4 High |
| Closed Top drum | 60 | Ø 400 | 598 | 2.50 | 2.500 ± 0.100 | 4 High |

COMPONENTS

- 1- S 70 x 6 & S38x6 Bungs
- 2- 2" Bungs + 2" Bungs vented valve
- 3- 60 MM Pilfer guard Cap+Vent (new design)
- 4- 60 MM Cap + with vented valve
- 5- 2" Metal Over Cap
- 6- Tempar Proof Plastic lock & Seal
- 7- 38 MM Screw Cap
- 8- Combination Spanner for 60mm cap, 2"bungs, S70 & S38



JERRYCANS



30 Liter

25 Liter

20 Liter

25 Liter Round

20 Liter Round

The most versatile container in the AL-BABTAIN RANGE

The "Square Round" & Round Jerrycans configuration give an excellent freight factor of 1.3 making optimum use of international standards pallet size, with stacking eight across which is the internal width of an ISO freight container. The dimension also provides optimum usage of truck space. Two different versions of containers are manufactured, according to the height of stacking requires in 2 & 4 high.

The heavy weight containers are approved for the carriage of dangerous goods.

Containers are available with either a standard 60mm screw cap fitted with a PVC/ butyl rubber / PE sealing ring or 2" bungs fitted with PE sealing ring these gives a very efficient sealing.

| Product Type | Capacity (Liters) | Overall Dimensions | | | Weight (Kg) | Wall Thickness (mm) |
|----------------|-------------------|--------------------|---------|--------|----------------|---------------------|
| | | Length | Breadth | Height | | |
| Jerrycan | 30 | 283 | 283 | 512 | 1.100 to 2.000 | 1.2 - 1.6 |
| Jerrycan | 25 | 283 | 283 | 442 | 1.100 to 1.300 | 1.1 - 1.3 |
| Jerrycan | 20 | 283 | 283 | 370 | 0.850 to 1.200 | 0.9 - 1.3 |
| Round Jerrycan | 25 | Ø 300 | | 480 | 1.275 to 1.350 | 1.3 - 1.4 |
| Round Jerrycan | 20 | Ø 300 | | 400 | 1.000 to 1.250 | 1.2 - 1.3 |

HANDLE WARE



5 Ltr

4 Ltr

3.78 Ltr
(1 US Gal)

3.78 Ltr
(1 US Gal)

3.50 Ltr

3.78 Ltr
(1 US Gal)

AL-BABTAIN range of handleware containers are designed in rectangular and cylindrical shapes. These are ideally suited as packaging for household chemicals. Amongst their many other uses are for Motor Oil, Distilled Water, Antifreeze, Vegetable Oil, Detergents and disinfectants. For further details on suitability you can contact AL-BABTAIN PLASTIC DIVISION.

| No | Product Type | Capacity (Ltrs) | Dimension (mm) | | | Weight (gm) | Min. Wall Thickness (mm) |
|----|--------------|-----------------|------------------|---------|--------|-------------------|----------------------------|
| | | | Length | Breadth | Height | | |
| 1 | Rectangular | 5 | 182 | 128 | 284 | 200 ^{±5} | 0.7 |
| 2 | Rectangular | 4 | 195 | 110 | 272.5 | 175 ^{±5} | 0.5 |
| 3 | Rectangular | 3.78 | 188 | 103 | 308 | 150 ^{±5} | 0.5 |
| 4 | Cylindrical | 3.78 | Ø 139.6 | | 318.5 | 120 ^{±5} | 0.4 |
| 5 | Cylindrical | 3.50 | Ø 139.6 | | 300 | 115 ^{±5} | 0.4 |
| 6 | Cylindrical | 3.78 | Ø 159.0 | | 300 | 150 ^{±5} | 0.5 |

PLASTIC CONTAINERS

Our Containers are in different types and ranges from 3.5ltr. up to 220ltr. This wide range make them ideal source for packaging of almost all types of chemicals.



PLASTIC PALLET

Our Pallets are made from Polypropylene (Thermo Plastic) injection molded materials and are available in different sizes with high racking and dynamic load capacity.



INSULATION

AL-BABTAIN is the pioneer in Polyurethane foam since 1979. Our product is dedicated to quality and reliability.



شركة الباطين لصناعة البلاستيك والمواد العازلة المحدودة

س . ت ٥٦٥٣٥١٠٠ - الدمام - المدينة الصناعية الأولى، ص . ب ٤٩٤ - الخبر ٣١٩٥٢ - المملكة العربية السعودية
البلاستيك : تلفون : ٨٤٧١٦٩ / ٨٤٧١٦٣ - ١٣ - فاكس : ٨٤٧٣٠٥٢ - العوازل : تلفون : ٨٤٧١٥٨ / ٨٤٧١٥٤ - ١٣ - فاكس : ٨٤٧١٣٦٢ - ١٣

AL BABTAIN PLASTIC & INSULATION MATERIALS MFG. CO. LTD

C.R. 2051005356 - Dammam - 1st. Industrial Area, P. O. Box 494, Al-Khobar 31952, Saudi Arabia

Plastic: Tel.: 013 - 847 1609 / 847 1613, Fax: 013 - 847 3052 Insulation: Tel.: 013 - 847 1758 / 847 1754, Fax: 013 - 847 1362

E-mail:- info@albabtainplastic.com

www.albabtainplastic.com

